



UNIVERSAL CLEANER PLUS

OIL SPONGE UC+ is an innovative powerful, all-purpose, water-based cleaner that is fit for the toughest industrial needs.

Bio-Driven Technology is a proprietary blend of Class 1, ATCC certified microbes; OIL SPONGE UC+ will assist in converting oils, greases, and fat removed during the cleaning process to safer carbon dioxide and water effluent. This earth friendly, bio-compatible cleaner is ideal for enhancing the efficiency of any system that currently utilizes a microbial treatment.

OIL SPONGE UC+ is strong enough to remove substances ranging from general industrial cleaning to heavier greases and oils. As it is readily bio-degradable, it contains no Butyl, Phosphates, Nitrates, Chlorinated Solvents, or Petroleum by-products. OIL SPONGE UC+

meets the California South Coast Air Quality Management District cleaner specifications by containing less than 50 g/l VOC in dilution.

OIL SPONGE UC+ requires no additional handling or storing precautions. It is safe to store in normal settings and is both user and eco friendly.

OIL SPONGE UC+ is an amazing product that will not only reduce your carbon footprint, but also meets all the standards that are considered to be an environmentally conscious cleaner.

SIZE	PART #	PACK
1 gallon	80001	4/cs 48 cs/plt
5 gallon	80005	48/plt
55 gallon	80055	4/plt



OIL SPONGE UC+ UNIVERSAL CLEANER PLUS CLEANER CONCENTRATE IS:

A Low-VOC, water-base degreaser with a powerful microbial package added for the toughest industrial needs.

BENEFITS:

- → Non-toxic
- → No corrosive enhancers (as common in most heavy-duty degreasers)
- → No petro-chemicals
- → ATCC Bacterial Package for Complete Degreasing
- → Readily Bio-Degradable
- → Compatible with oil water separators

FEATURES:

- Contains no phosphates, nitrates, sulphates, caustics, terpenes, chlorinated solvents or petroleum by-products.
- → Less than 50g/IVOC in dilution as tested by SCAQMD
- → pH 9-9.5 in concentrate form

OIL SPONGE UC+ CAN BE USED IN:

- → Mop Buckets
- → Parts Washers
- → Power Sprayers
- → Soak Tanks
- → Spray Bottles
- → Wipe Applications

DIRECTIONS FOR USE:

Dilute solution to proper ratio; apply by spray or wipe method. Some mechanical motion may be required to assist in the agitation of the soils. Rinse clean; repeat if necessary.

OIL SPONGE UC+ IS NEEDED IN THE FOLLOWING AREAS:

- → Automotive Mfg. & Repair (Interior-to-Exterior-to-Engine Degreasing)
- → Bars, Bistros, & Restaurants
- → Hospitals & Other Institutions
- → Hotels & Motels
- → Household
- → Machine Shops
- → Military
- → Shipyards & Marinas (Bilges-to-Decks)

OIL SPONGE UC+ CAN BE STORED IN GENERAL CHEMICAL BAYS KEPT BETWEEN 32° TO 120°F.

DILUTION GUIDELINES: Type, age and build-up of soils will determine dilution concentration and need to be determined on-site through simple application testing.

HEAVY-DUTY: 1:1 to 1:20 MEDIUM-DUTY: 1:20 to 1:60 LIGHT-DUTY: 1:60 to 1:200

PHYSICAL CHARACTERISTICS:

APPEARANCE: Peach Colored Liquid

ODOR: Green Apple Specific Gravity: 1.02 Vapor Density: (Air=1) >1

PH: 9-10

SOLUBILITY IN WATER: 100% PERCENT VOLATILE: >89% FREEZING POINT: ca 32º f

voc: <10g/L



